

Belt Fabric Printer

导带式纺织布打印机

Up to 108sqm/h 高达108平米/小时

Disperse/Textile Pigment/ Acid/ Reactive Ink 发散/颜料/酸性/活性墨水

Two/ Four Epson Official Supplied i3200 Heads 2/4爱普生i3200喷头


BFP-740



 SINO
COLOR

Belt Fabric Printer | BFP-740


● Features 特点



Epson Official Supplied i3200 Printheads

Two or four heads optional. The speed and quality are guaranteed.

配备Epson原装i3200喷头，速度与品质的保证



Tension Type Media Feeding and Take-up System

Apply to material with different elasticity.


标配材料张力系统，可适应不同弹力的材料稳定走布



Anti-collision system

Printer will automatically stop when the carriage hit any unexpected object. And support to continue printing. Reduce the material waste.


防撞系统，当平台出现异物或者打印材料翘起阻挡小车移动，设备会自动暂停并支持断点续打避免额外的材料浪费



Standard Belt Cleaning System

The water jet and brush roller are equipped to guarantee the clean of the belt.

标配导带水洗，擦拭系统，去除导带上残留的纺织品碎末，保持导带清洁



Super Wide Heating Device

Guarantee the drying of ink on fast speed printing mode. Get ready for after-treatment.

前置超宽的加热组件，配合高速模式上墨水的烘干，为后处理做好准备



● Specification 参数

Model No. 产品型号		BFP-740	
Printhead 喷头	Type 喷头类型	2 x Epson i3200 / 4 x Epson i3200	
	Nozzles 喷嘴数量	3200 Nozzles Per Head	
Max Material Thickness 高度调节		3cm	
Max Printing Width 打印尺寸		1.8m	
Resolution (dpi) 打印精度		1440 dpi	
Media Types 适应耗材		Cotton, Viscose, Polyester, Polyamide, Silk, Wool 棉, 雪纺, 涤纶, 尼龙, 真丝, 羊毛	
Ink 墨水	Type 墨水类型	Disperse/ Pigment/ Acid/ Reactive Ink 发散/颜料/酸性/活性墨水	
	Color 墨水颜色	4 Color / 5 Color	
	Droplet 墨滴大小	1.5 – 21pl Variable	
Speed 速度	Standard 标准模式	80 sqm/h	150 sqm/h
	Quality 精细模式	40 sqm/h	75 sqm/h
	Photo 照片模式	25 sqm/h	50 sqm/h
Feed & take up 收放布系统		Tension Media Feeding & Take-up System (Standard)	
Cleaning 清洗系统		Automatic Cleaning, Anti-Clogging Flash Function & Capping System 自动清洗, 闪喷, 封喷头	
Heating System 加热系统		IR Heater & Front Ultra-wide Heating Device	
Cooling System 冷却系统		Cooling Fan Equipped	
Environment 工作环境		Temperature: 20-28 ℃, Humidity: 40%-60%	
Rip Software 图像处理		Maintop/ Photoprint (Optional)	
Control Software 控制软件		SinoColor Print Console	
Interface 输入接口		USB 3.0	
Operation System 操作系统		Windows 7 / XP / 10	
Power 电源消耗		Machine 50 / 60HZ, 110 / 220V	

Specifications are subject to change without notice. 以上参数可能随机器版本改变，请以厂家最新数据为准。