

爱普生 i3200-U喷头
Epson i3200-U Printheads

可变墨滴
Variable Dot

负压系统
Negative Pressure System

白色和光油
White & Varnish

爱普生 i3200-U喷头 宽幅UV平板打印机

宽幅 250x130cm




PRECISIONCORE
PRINTHEAD
powered by EPSON

● 特点 Features



最新的爱普生i3200-U工业级喷头
专注高速打印

Latest Epson Industrial Printhead i3200-U
Equipped. Focus on super fast speed printing.




内置独立双高功率抽风机, 确保吸力强劲

Double built-in high-power independent vacuum
pump. Guarantee the powerful suction.



配置高级的负压系统。稳定供墨, 简化多头
设备维护。

Simply and effectively ensure the continuous ink
flow, and easy maintenance for multi-heads
equipment.



标配自动测高功能

Automatic media height detecting system is
equipped, provide great help for setting the
proper print height.



1.7米超长内嵌旋转装置可选, 增加设备附
加值

1.7m ultra-long built in rotary device is optional.
Fit for different type of cylinder subject. Increase
the additional value of machine.

★ 高精度的机器框架确保完美的打印分辨率

The high precision machine frame ensures perfect print resolution

★ X轴的齿轮固定部件采用一次成型技术进行加工, 以确保最高分辨率标准

X axis' s gear fixation components are processed with one-time molding technology

★ X轴配备双导轨, 确保小车的平稳运动

X axis is equipped with dual guide rail which ensures smooth movement of carriage

★ Y轴采用丝杠传动方式, 比皮带传动精度高得多

Y axis is using screw drive transmission mode



● 参数 Specification

| | | |
|--------------|---------------------|--|
| 型号 | Model No. | FB-2513S |
| 喷头 | Printhead | 4 × Epson i3200-U |
| 精度 | Resolution | Max 2400 dpi |
| 耗材 Media | 厚度 Thickness | Max 12 cm |
| | 尺寸 Size | 2500 × 1300 毫米 |
| | 种类 Types | 玻璃, 亚克力, 陶瓷, 金属, 纸, 木板, 皮革, PVC, PP, PE, PTFE等 Glass, Acrylic, Ceramic, Metal, Paper, Wood, Leather, PVC, PP, PE, PTFE Etc. |
| 速度 Speed | 草图 Draft | 80 平米/小时 (CMYK) |
| | 标准 Production | 52 平米/小时 (CMYK) |
| | 精细 Quality | 38 平米/小时 (CMYK) |
| 墨水 Ink | 墨水 Type | UV墨水 |
| | 颜色 Color | CMYK/CMYK + W/CMYK + W + V |
| | 墨瓶 Capacity | 500 毫升 |
| | 干燥 Dry System | UV光固化系统 |
| 系统 | PC Operation System | Windows 7/XP/10 |
| 环境 | Environment | 温度: 20-28°C, 湿度: 40%-60% |
| 软件 | Rip Software | 蒙泰 (标配) / Photoprint (选配) |
| 图片格式 | Image Format | TIFF, JPEG, EPS, PDF... |
| 电源 | Power | Max 3.6KW, AC 50/60Hz, 220V(±10%)>12A |
| 尺寸 Size | 机器 Machine | L4120 × W2000 × H1400 mm |
| | 包装 Packing | L4220 × W2100 × H1610 mm |
| 重量 Weight | 机器 Machine | 850 KG |
| | 包装 Packing | 1000 KG |

以上参数可能随机器版本改变, 请以厂家最新数据为准。Specifications are subject to change without notice.